

MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)		Fastener Schedule				DF/SP Allowable Loads (Lbs.) <sup>1,2</sup>	
					Nails <sup>6</sup>		Bolts <sup>5</sup>		F1 <sup>3</sup> 160%	F2 160%
			W	L	Qty	Type	Qty	Type		
B23	--	12	2	2-5/8	6	16d	--	--	--	--
B24	--	12	2	3-5/8	8	16d	--	--	--	--
BL3	A33	12	1-1/4	3-1/16	8	10d	--	--	735	285
BL4	A44	12	1-1/4	4-13/16	10	10d	--	--	720	275
BL6	--	12	1-1/4	6-9/16	12	16d	--	--	--	--
BL8	--	12	1-1/4	8-5/16	14	16d	--	--	--	--
B66	A66	12	1-1/2	6	--	--	4	3/8	710	335
B88	A88	12	2	8	--	--	6	3/8	620	305

1) Allowable loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Loads shown are for a single corner brace.

3) Corner braces are required on both sides to achieve F1 loads in both directions.

4) Minimum member thickness is 3".

5) Bolts shall conform to ASTM A 307 or better.

6) **NAILS:** 16d nails are 0.162" dia. x 3-1/2" long.