

| MiTek Stock No. ² | Ref. No. | Steel Gauge | Dimensions (in) | | | Fastener Schedule ³ | | | | | DF/SP Allowable Loads (Lbs.) | | | | | |
|---------------------------------|----------|----------------|-----------------|--------|-------|--------------------------------|------|-------------|-------|-------------|---------------------------------|-----------------------------|------------|------------|------------|------------|
| | | | W | H | L | Min/ Max | Stud | | Plate | | | Uplift ¹ 160% | F1 160% | F2 160% | F3 160% | F4 160% |
| | | | | | | | Qty | Type | Qty | Type | Type | | | | | |
| RSPT4 | RSP4 | 20 | 1-1/2 | 4-1/8 | -- | -- | 4 | 8d x 1-1/2 | 4 | 8d x 1-1/2 | 460 | 255 | 300 | -- | -- | |
| SPT22 | SP1 | 20 | 1-9/16 | 4-3/8 | 3-1/2 | -- | 4 | 10d | 4 | 10d | 735 | 535 | 275 | -- | -- | |
| SPT24 | SP2 | 20 | 1-9/16 | 5-5/8 | 3-1/2 | -- | 6 | 10d | 6 | 10d | 1090 | 535 | 275 | -- | -- | |
| SPT44 | -- | 20 | 3-9/16 | 6-3/4 | 6-1/2 | -- | 6 | 16d | 6 | 16d | 1315 | 845 | 275 | -- | -- | |
| RSPT6 | SSP | 18 | 1-1/2 | 5-7/16 | -- | -- | 4 | 10d x 1-1/2 | 4 | 10d x 1-1/2 | 650 | -- | -- | -- | -- | |
| RSPT6-2 | DSP | 18 | 2-3/4 | 5-7/16 | -- | -- | 8 | 10d x 1-1/2 | 6 | 10d x 1-1/2 | 900 | -- | -- | -- | -- | |
| TSP | TSP | 16 | 1-5/8 | 7-7/8 | -- | Min | 3 | 10d x 1-1/2 | 3 | 10d x 1-1/2 | 465 | -- | -- | -- | -- | |
| | | | | | | Max | 9 | 10d x 1-1/2 | 6 | 10d x 1-1/2 | 830 | 365 | 190 | 210 | 235 | |
| | | | | | | | | | | 10d | 870 | | | | | |

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) SPT22, SPT24, and SPT44: the nails fastened to the wide face of the stud must be driven 30° from the perpendicular on the horizontal plane.

3) **NAILS:** 8d x 1-1/2 nails are 0.131" dia. x 1-1/2" long, 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long.