

Option	Skewed ^{1,3,4,5}	Sloped Seat ^{2,3,4}	Sloped / Skewed ^{1,2,3,4,5}	Inverted Flange ⁴
Range	1° to 67-1/2° when width is 1-3/4" or less. 1° to 50° on all others.	1° to 45°	See Sloped Seat and Skewed	Not available in widths less than 2-1/4"
Allowable Loads	100% of table load. 75% of uplift load on skews greater than 15°.	100% of table load	80% of table load. 75% of uplift load on skews greater than 15°.	100% of table load. 65% of table load when nailing into the support members end grain.
Ordering	Add <i>SK</i> , angle required, right (<i>R</i>) or left (<i>L</i>), and square cut (<i>SQ</i>) or bevel cut (<i>BV</i>) to product number. Example: IHF23925_SK45R_BV	Add <i>SL</i> , slope required, and up (<i>U</i>) or down (<i>D</i>), to product number. Example: IHF23925_SL30D	See Sloped Seat and Skewed Example: IHF23925_SK45R_SL30D_BV	Add <i>IF</i> , to product number. Example: IHF23925_IF

- 1) Skewed hangers with skews greater than 15° may have all joist nailing on outside flange.
- 2) Sloped or sloped / skewed hangers with slopes greater than 15° may have additional joist nails.
- 3) For skewed hangers, the required cut type (square or bevel) of joist member may vary based on skew angle and width of hanger. Some square cut hangers will require custom pricing due to welded back plate.
- 4) Modifications to IHFL or IHF hangers do not feature seat cleats or optional nailing.
- 5) Skewed hangers may require web stiffeners to be installed in order to facilitate joist nail installation.