

READY-FEED CONVEYOR

A multiple-strand chain infeed conveyor designed to be integrated with MiTek® component saws.



PHYSICAL DATA

Length	10'	20'	30'	40'
Dimensions	10' L x 18' 2" W x 36" +/-3" H	20' L x 18' 2" W x 36" +/-3" H	30' L x 18' 2" W x 36" +/-3" H	40' L x 18' 2" W x 36" +/-3" H
Weight	3,000 lbs	6,000 lbs	9,200 lbs	12,500 lbs
Motor	5 hp	5 hp	5 hp	7-1/2 hp

PERFORMANCE DATA

Speed	25 ft per minute			
Direction of travel	Forward and reverse			
Controls	Tape switch			
System Length	10'	20'	30'	40'
Weight Capacity <i>When evenly distributed</i>	10,000 lbs	15,000 lbs	25,000 lb	35,000 lb
Board Length	4' to 20' long	4' to 20' long	4' to 20' long	4' to 20' long
Board Width / Depth	Unlimited	Unlimited	Unlimited	Unlimited

FEATURES

- Creates supply buffer for sawyer.
- Adjustable height enables gravity to work to your advantage.
- Tape switch controls give operator more flexibility and freedom of movement.

ELECTRICAL DATA

Electrical specs

5 hp

7-1/2 hp

208/230/460/575 VAC

208/230/460/575 VAC

3-phase

3-phase

60 Hz

60 Hz

FLA plus control amps

14.6/13.2/6.6/5.0

21.1/19.1/9.6/7.6

Disconnect protection

30/30/15/10

45/40/20/17.5

Tape switch controls

120V

120V

SAFETY DATA

E-stops

Pushbutton

Safety compliance

UL (panels), OSHA

Labels

Bilingual or ISO safety labels

OPTIONS

→ Auto-feed feature